

UNIOIL ST

Synthetic sulphited softener

TYPICAL PROPERTIES

Appearance : Milky liquid Active Substance : $50 \pm 1\%$ pH (10% sol.) : 7.0 ± 0.5 lonic Character : Anionic

DESCRIPTION

UNIOIL ST is a multipurpose softening agent for different types of leathers and especially for double-face, resulting with supple and soft leathers. It can be applied at a wide pH range such as, in pickling, in tanning and in retanning due to its good electrostability against different agents. **UNIOIL ST** outstands with its excellent penetration capacity without creating greasy hair in double-face productions. It is compatible with all post-tanning agents such as syntans, resins and dyestuffs.

APPLICATION

UNIOIL ST is recommended for fur-skin and double-face 1-2 g/l in pickling; 2-3 g/l in chrome tanning; 2-4 g/l in fatliquoring process. **UNIOIL ST** gives satisfactory results for softy-upper and lamb-suede-garment leathers.

PACKAGING, STORAGE AND SHELF LIFE

Available in 120 kg drums or in IBC. Store in accordance with local regulations. Keep the lid closed when not in use. Store in a dry place and protect from direct sunlight. Shelf life is 12 months from the date of manufacture when stored in its original package. For more information see Safety Data Sheet.